

ULTRA XR CTOF

Features & Benefits

A versatile, end-to-end finishing environment, the Ultra® XR Closed-Top Open-Front (CTOF) allows for vehicles to be filled, primed, sealed, painted and cured in one location. The Ultra XR CTOF is fully integrated with REVO Accelerated Curing Systems, eliminating bottlenecks and adding speed and flexibility to your shop's processes.

Top-of-the-Line Controls

The Ultra XR CTOF comes standard with GFS' LOGIC 4 control panel. This premium panel provides complete control over the booth. User-programmable, intuitive controls include dual VFDs, a 10-inch color interface and nine customizable flash and cure profiles that make it easy to tailor booth cycles for different coatings.

Excellent Airflow & Lighting

Maximizing the effectiveness of the downdraft airflow, the Ultra XR CTOF features GFS' exclusive Controlled Airflow Ceiling. This fully-filtered ceiling creates a protective envelope of air around the vehicle, while secondary zones keep overspray off booth walls and contaminants out of the paint job. Strategically placed ceiling lights eliminate shadows and provide excellent illumination for prepping and painting.

Sturdy, Flexible Construction

The Ultra XR CTOF is available in a flexible, dual-bay configuration. White pre-coated, dual-skin insulated panels provide a smooth fit and finish on the booth's sidewalls, while front curtains enclose the booth and divider curtains separate the bays.

REVO System Integration

Integrated directly into your Ultra XR CTOF, the REVO Speed or Rapid improves paint shop efficiency by quickly curing filler and coatings. A built-in overhead rail system enables the REVO Speed or Rapid to easily move alongside the vehicle or panels, to quickly and thoroughly cure all coatings. To make the solution fully NFPA 33 compliant, pressurized power rails prevent overspray from entering the rails, and the REVO System can be moved outside the spray area or stored in a pressurized parking garage when not in use.

